

## COMBODOCK™4

Fourth Generation adds new features to quickly connect 3.5" drives through FireWire 800/400/USB



Drive not included.

### More features for accessing bare IDE 3.5" drives!

ComboDockv4 is a perfect solution for anyone who wants highest speed FireWire transfer rates and access to bare 3.5" IDE drives. It quickly attaches drives via FireWire 800 (400 compatible) or USB. Dual FireWire 800 ports allow daisy-chaining for more versatility.

### Gobs of utility

Generation 4 provides plenty of options. In addition to its bright new color, it has new power control features and multiple powering options. Attach it to any IDE drive (or even SATA drive, using an optional adapter). Power it via a +12V adapter (included), or power it via a standard disk drive 4-pin molex power source. Because it's based on the OXUF922 chip, FireWire transfer rates are really fast.

### Using it is easy!

Just connect the drive to the Dock, plug in power and attach a FireWire or USB cable to a host computer. That's all it takes. For more protection to the drive, a mounting plate is attached to the dock to protect the drive's circuitry.

### Exclusive LED indicators

Generation 4 is loaded with indicators: FireWire attached, USB attached, +12V input jack active, disk drive power input jack active and +5V/+12V out operational. It makes a technician's work much easier. These simple features are immensely valuable when troubleshooting a drive. It even has an on/off switch for safe drive power up and power down.

### Rugged design, built to last

Grab it and go - Generation 4 is tough as nails and built to last. The small and rugged case is built from aluminum for durability.

### Tested and Formatted

When you buy a drive from WiebeTech, we go the extra mile to make sure your product works for your computer. Before your order is shipped, it is individually tested and formatted to your needs whether it is Mac, PC or both.

## FEATURES

### Dual FireWire 800 Ports

Allow daisy chaining.

### USB 2.0 Port

Allows attachment of USB hosts.

### +12V DC Power In

Allows powering using the included AC adapter.

### Disk Drive Power In

Allows powering from standard 4-pin drive power connectors as is found in most computers.

### +12V Power Input LED

Identifies valid power input source on +12V input jack.

### Disk Drive Power In LED

Identifies valid power input source on 4-pin drive power input socket.

### +5V, +12V LEDs

Verifies that power output is operational.

### On / Off Switch

Allows Power Up / Down.

### FireWire Host Detection LED

Identifies valid FireWire host attachment.

### USB Host Detection LED

Identifies USB attachment.

### IDE Cable Connector

Supports attachment to drives inside of computers.

### Aluminum case

Briefcase tough; excellent heat dissipation.

### Small size

Fits in a pocket.

## TECHNICAL SPECIFICATIONS

### Interface

Two daisy-chainable FireWire 800 ports: OXUF922

USB2: OXUF922

### Power

External power supply: 100-240VAC +12V / +3A  
(Included)

Power input: +12V DC input jack; +12V / +5V standard  
disk drive 4-pin jack (Molex connector)

Power output: +12V / +5V

Power switch: On / Off

### LED Indicators

FireWire attached

USB attached

+12V input jack active

Disk drive power input jack active

+5V power operational

+12V power operational

Access

### Data Speeds

FireWire 800: up to 800 Mbps

FireWire 400: up to 400 Mbps

USB2 port: up to 480 Mbps

### Operating Temperature

50° - 85° Fahrenheit (10° - 30° Celsius)

### Operating Humidity

5% to 95%, noncondensing

### Drive Compatibility

3.5" IDE drive

### Operating System

Windows XP

Macintosh OS X

Linux distributions that support FireWire

### Shipping Weight

3 lbs. (including AC adapter)

### Dimensions

3.2" x 2.2" x 0.95" (81mm x 56mm x 24mm) exclusive of  
attached plates, drives and cables

### Certification

FCC, CE

### INCLUDES:

Order code: CDKV4

ComboDockv4

Ribbon cable

AC adapter

FireWire 800-400 cable

Drive bottom plate and screws

Information CD

Limited Warranty Statement

### First-class Tech Support

We don't want anything to go wrong with your WiebeTech product. But if it does, Tech Support is standing by and ready to help. We offer 90 days of free phone support at 1-866-744-8722. After 90 days, email support is available at [support@wiebetech.com](mailto:support@wiebetech.com).