

FEATURES

Write-blocked

Protects drive's contents by preventing disk writes. Uses industry-proven WiebeTech write-block technology.

Daisy-chained Dual FireWire 800 Ports (400 compatible); Single USB2 port

Endless configuration capabilities.

Write-block feature active LED

Identifies write protection technology is operational.

FireWire Host Detection LED

Identifies valid FireWire host attachment.

USB Host Detection LED

Identifies USB attachment.

+12V Power Input LED

Identifies valid power input source on +12V input jack.

Disk Drive Power In LED

Identifies valid power input source on 4-pin drive power input socket.

+5V, +12V LEDs

Verifies that power output is operational.

+12V DC Power In

Allows powering using the included AC adapter.

Disk Drive Power In

Allows powering from standard 4-pin drive power connectors as is found in most computers.

On / Off Switch

Allows Power Up / Down.

Plug and Play

No new drivers necessary for usage with Windows XP, Mac OS X and Linux distributions that support FireWire.

Aluminum case

Briefcase tough; excellent heat dissipation.

Small size

Fits in a pocket.

INCLUDES:

Forensic SATADock v4
AC adapter
Order code: FSDKV4
FireWire 800-400 cable
FireWire 800-800 cable
Drive bottom plate and screws
Information CD
Limited Warranty Statement

TECHNICAL SPECIFICATIONS

Interface

Two daisy-chainable FireWire 800 ports: OXUF924
USB2: OXUF924

Power

External power supply: 100-240VAC +12V / +3A (Included)
Power input: +12V DC input jack; +12V / +5V standard disk drive 4-pin jack (Molex connector)
Power output: +12V / +5V
Power switch: On / Off

LED Indicators

Write-block technology active
FireWire attached
USB attached
+12V input jack active
Disk drive power input jack active
+5V power operational
+12V power operational
Access indicator

Drive Connectors

Combined SATA data/power connector

Data Speeds

FireWire 800: up to 800 Mbps
FireWire 400: up to 400 Mbps
USB2 port: up to 480 Mbps

Operating Temperature

50° - 85° Fahrenheit (10° - 30° Celsius)

Operating Humidity

5% to 95%, noncondensing

Drive Compatibility

Any size SATA drive

Operating System

Windows XP
Macintosh OS X
Linux distributions that support FireWire

Shipping Weight

3 lbs. (including AC adapter)

Dimensions

3.2" x 2.2" x 0.95" (81mm x 56mm x 24mm) exclusive of attached plates, drives and cables

Certification

FCC, CE
ROHS compliant

First-class Tech Support

We don't want anything to go wrong with your WiebeTech product. But if it does, Tech Support is standing by and ready to help. We offer 90 days of free phone support at 1-866-744-8722. After 90 days, email support is available at support@wiebetech.com.